


# Weidmüller Tools & Crimp Set

## Crimp Set

Weidmüller's crimp sets for cutting, stripping and crimping of wire-end ferrules provide operating equipment oriented towards practical application. The set includes crimping tool up to 10 mm<sup>2</sup> hexagon, stripping tool and wire-end ferrules in DIN colour code.

### Crimping tools for wire end ferrules, with and without plastic collars

PZ 10 HEX can process wire-end ferrules with or without plastic collars in the cross-section range of 0.14 to 10 mm<sup>2</sup> (AWG 26 to 8). The hexagonal crimp produces a rounded crimp shape with a small diameter and is ideal for situations where the clamping space is limited.



### Stripping tools for finely stranded and solid conductors

stripax® stripping tools guarantee you a consistent stripping result in accordance with the DIN standard. Thanks to the self-adjusting blade, stripax automatically adapts to the respective conductor cross-section. Remove conductor insulation with cross-sections ranging from 0.8 to 10 mm<sup>2</sup>.



## CRIMP SET PZ 10 HEX D

Set including crimping tool up to 10 mm<sup>2</sup> hexagon, stripping tool and wire-end ferrules in DIN colour code.

Order number: 1542260000

1 setti 219€

3 settiä 195€/setti

Tarjous on voimassa tilaukselle 31.12.2017



## Cutting

**KT 8**  
9002650000

max. 8 mm  
max. 16 mm<sup>2</sup>

**KT 22**  
1157830000

max. 22 mm  
max. 25 mm<sup>2</sup>

**KT 45 R**  
9202040000

max. 45 mm  
max. 400 mm<sup>2</sup>

**SUPER CUT**  
9205150000

Cu max. 1.2 mm / AWG16

**SCISSORS 2K**  
9918230000



## Stripping

**stripax®**  
9005000000

0.08 - 10 mm<sup>2</sup>  
PVC only

**stripax® ULtimate**  
1468880000

0.25 - 6 mm<sup>2</sup>  
PVC + halogen free

**AM 16**  
9204190000

5 - 17 mm

**IE-CST**  
9204350000

2.5 - 8 mm

**Stripper round top**  
9918050000

8 - 13 mm  
0.2 - 4 mm<sup>2</sup>



## Crimping

**PZ 10 HEX**  
1445070000

0.14 - 10 mm<sup>2</sup>

**PZ 10 SQR**  
1445080000

0.14 - 10 mm<sup>2</sup>

**PZ 6 Roto L**  
1444050000

0.14 - 6 mm<sup>2</sup>

**CTI 6**  
9006120000

0.5 - 6 mm<sup>2</sup>

**EPG 60**  
2453810000

6 - 300 mm<sup>2</sup>



## Screwing & Testing

**SlimLine Set**  
1274750000

**VT LCL**  
2436670000

12 - 1000 V AC

**VT M**  
2436680000

> 2,5 mT

**VT CTL**  
2436690000

0 - 500 kΩ

**VT**  
9918950000

12 - 690 V AC/DC  
CAT III 600 V