


BES 516-300-S279
 BES033J

PNP
 NO
 flush mountable

BALLUFF
sensors worldwide



PX0239

Electrical data:

Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	50 mA
Hysteresis max (H)	15 %
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V
Utilization category	DC 13
Switching output	PNP
Switching element function	NO
Time delay before availability	10 ms
No-load supply current damped	= 25 mA
Operating frequency (f)	1500 Hz
Voltage drop max. static	0,5 V
Connection	Cable
Electrical type	DC
Off-state current max (Ir)	80 µA
Ripple max. of Ue	= 15 %

Mechanical data:

Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	PBTP
Number of wires	3-wire
Assured operating distance	0...1,6 mm
Cable code designation	LiYY-O
Repeat accuracy max. (R)	10 %
Rated operating distance (sn)	2 mm
Ambient temperature max	+70 °C
Mounting	flush mountable
Housing material	Gd Al Si 12

General data:

Degree of protection IP	IP65
Additional text 1	Miniature fuse according IEC60127-2 Sheet 1, ≤ 2 A (quick/acting). Fuse must be in load line. Fuse must not be in outp. line
Output indication	yes
Short circuit protected	no
Approval	CE
Protected against polarity reversal	yes

Wiring:

