

Crimping tools for cable end sleeves

acc. to DIN 46228 page 1 and 4



12640/12641
Square crimping



12646/12647
Trapezoid crimping

| Part-No. | cross-section range | | description | length | weight kg/pcs. |
|--------------|---------------------|--------------|---|--------|----------------|
| 12640 | Single | 0,08 - 10 mm | Crimping tool with ratchet and square crimping. Only one die for the whole cross-section range with ferrule insertion from the side. | 200 mm | 0,33 |
| | Twin | 0,5 - 4 mm | | | |
| 12641 | Single | 2,5 - 16 mm | | 200 mm | 0,33 |
| | Twin | 6 - 10 mm | | | |
| 12646 | Single | 0,14 - 6 mm | Crimping tool with ratchet and trapezoid crimping. Only one die for the whole cross-section range with front insertion. | 230 mm | 0,50 |
| | Twin | 0,5 - 4 mm | | | |
| 12647 | Single | 10 - 16 mm | | 230 mm | 0,55 |
| | Twin | 6 - 10 mm | | | |

Remark: Tools with high precession crimping and an excellent power gear ration.



05140
Square crimping

05141
Tool with case

05144
Square crimping

| Part-No. | cross-section range | | description | length | weight kg/pcs. |
|--------------|---------------------|--------------|---|--------|----------------|
| 05140 | Single | 0,25 - 6 mm | Crimping tool without tool case | 130 mm | 0,42 |
| | Twin | 0,5 - 4 mm | | | |
| 05141 | Single | 0,25 - 6 mm | Part-No. 05144 , but with tool case | 130 mm | 0,42 |
| | Twin | 0,5 - 4 mm | | | |
| 05144 | Single | 0,08 - 16 mm | Crimping tool with ratchet and square crimping. One switchable die with front insertion. | 190 mm | 0,48 |
| | Twin | 0,5 - 10 mm | | | |

Remark: Part-No. 05140/41. Perfect in ergonomics and design. The design with the optimized power gear ratio realize a fatigue-proof work. Max. ferrule length in one crimping operation 12 mm and 18 mm in two crimping operations.

Part-No. 05144 High quality crimping tool. Only with one crimping die for cable end sleeves in a cross-section range of 0,08-16 mm and a length up to 15 mm. With switchable crimping range (working range 1 = 0,08-10 mm , working range 2 = 16 mm).