








[Back](#)

Type CKW (conduit and cable fitting)

90° angled and folding 2-in-1 combined conduit and cable fitting. The CKW is a combination of our proven angle cable fitting and the EH conduit fitting

- Clamping around entire circumference, ensuring maximum tear-out strength
- Optimum strain relief for the cable due to iris-shaped lamellae
- No parts can get lost, as fitting does not have to be dismantled for assembly
- High protection to IP65 without additional parts
- Folding angle piece makes cable assembly easy



	RoHS compliant
	-40 – 110 °C transient 140 °C
	V0
	IP 65
	Mod. polyamide PA 6 Moulded seal: Buna N
	DB authorisation
	BS-certification

Type	Order no.	Colour	Connecting thread	Suited for Murrflex	EH mm	L mm	GL mm	LW mm	SW 1 / 2 mm	Pack qty.
Metric version										
CKW-M16x1,5/9	83584250	black	M16x1.5	M12 / P9	23.0	72.0	8.0	4.0 – 8.0	22 / 22	50
CKW-M20x1,5/16	83584256	black	M20x1.5	M20 / P16	32.0	83.0	9.0	6.0 – 12.0	27 / 27	50
CKW-M25x1,5/21	83584258	black	M25x1.5	M25 / P21	40.0	103.0	12.0	13.0 – 18.0	33 / 33	25
CKW-M32x1,5/29	83584260	black	M32x1.5	M32 / P29	50.0	123.0	12.0	18.0 – 25.0	42 / 42	25
Pg version										
CKW-Pg 09	83581050	black	Pg09	M12 / P9	23.0	67.0	8.0	4.0 – 8.0	19 / 19	50
CKW-Pg 11	83581052	black	Pg11	M16 / P11	28.0	75.0	8.0	5.0 – 10.0	22 / 22	50
CKW-Pg 16	83581054	black	Pg16	M20 / P16	37.0	85.0	11.0	10.0 – 14.0	27 / 27	50
CKW-Pg 21	83581056	black	Pg21	M25 / P21	39.0	100.0	11.0	13.0 – 18.0	33 / 33	25
CKW-Pg 29	83581058	black	Pg29	M32 / P29	50.0	120.0	11.0	18.0 – 25.0	42 / 42	25

Dimensional drawing

