










Back

Type BL (clamping bracket for types UH and UHG)

Optional bracket for UH and UHG.

- Additional mechanical retention of conduit in exposure to extreme stresses.



	RoHS compliant
	-40 – 110 °C transient 140 °C
	V0
	Mod. polyamide PA 6
	UR authorisation
	DB authorisation
	BS-certification
	FAR authorisation
	ABD authorisation

Type	Order no.	Colour	Suited for UH / UHG	B mm	H mm	T mm	Pack qty.
BL 09	83621406	black	09	29.0	10.0	12.5	100
BL 11	83621408	black	11	29.0	11.0	12.5	100
BL 16	83621410	black	16	34.0	12.0	15.0	100
BL 21	83621412	black	21	41.0	13.0	15.5	100
BL 29	83621414	black	29	50.0	14.0	16.0	50
BL 36	83621416	black	36	60.0	17.0	18.0	50
BL 48	83621418	black	48	72.0	19.0	18.5	50
BL 09	83621146	grey	09	29.0	10.0	12.5	100
BL 11	83621148	grey	11	29.0	11.0	12.5	100
BL 16	83621150	grey	16	34.0	12.0	15.0	100
BL 21	83621152	grey	21	41.0	13.0	15.5	100
BL 29	83621154	grey	29	50.0	14.0	16.0	50
BL 36	83621156	grey	36	60.0	17.0	18.0	50
BL 48	83621158	grey	48	72.0	19.0	18.5	50

FAR / ABD authorisation for colour
grey only

Dimensional drawing

