







Back

### Type UHG

Fixing cable protection conduits to plants and machines

- The additional plate protects the holder against torsion
- Simply snap in conduits
- Optimum connection of conduit to holder thanks to double grooves of holder
- Optional BL bracket for applications with high stresses



-  RoHS compliant
-  -40 – 110 °C transient 140 °C
-  V0
-  Mod. polyamide PA 6
-  DB authorisation
-  BS-certification

Type	Order no.	Colour	Suited for Murrflex	A mm	B mm	H1 / 2 mm	T mm	Y1 / 2 mm	Ø1 / 2 mm	Pack qty.
suitable for Murrflex EW and EWX										
UHG 09	83621250	black	M12/P9	7.5	46.0	23.0 / 2.0	12.5	15.0 / 24.5	4.5 / 6.2	100
UHG 11	83621252	black	M16/P11	7.5	46.0	23.0 / 2.0	12.5	15.0 / 24.5	4.5 / 6.2	100
UHG 16	83621254	black	M20/P16(S)	9.5	50.0	30.0 / 2.5	15.0	17.5 / 27.0	5.5 / 6.2	100
UHG 21	83621256	black	M25/P21(S)	11.5	57.0	38.0 / 2.5	16.0	21.0 / 30.7	6.5 / 6.2	100
UHG 29	83621258	black	M32/P29(S)	11.5	67.0	43.5 / 3.0	16.0	25.5 / 35.3	6.5 / 6.2	50
UHG 36	83621260	black	M40/P36(S)	11.5	77.0	51.0 / 3.5	18.5	30.5 / 40.0	6.5 / 6.2	50
UHG 48	83621262	black	M50/P48(S)	11.5	89.0	64.0 / 3.5	19.0	37.0 / 46.5	6.5 / 6.2	50

### Dimensional drawing

