










[Back](#)

Type UHF

Quick and easy connection of control cabinet to door

- Various fastening possibilities
- Fixing holes fit horizontal and vertical bar system in the control cabinet
- Conduits can still be rotated
- Pre-assembly of lower part possible
- High tensile strength thanks to double webs
- Brackets included in delivery



	RoHS compliant
	-40 – 110 °C transient 140 °C
	V0
	Mod. polyamide PA 6
	UR authorisation
	DB authorisation
	BS-certification
	FAR authorisation
	ABD authorisation

Type	Order no.	Colour	Suited for Murrflex	A mm	B1 / 2 mm	C mm	D mm	H1 / 2 mm	T mm	Y1 / 2 mm	Ø mm	Pack qty.
suitable for Murrflex EW and EWX												
UHF 16	83621610	grey	M20/P16(S)	9.5	35.0 / 12.0	15.0	27.0	35.0 / 5.0	38.0	17.5 / 11.3	5.5	100
UHF 21	83621612	grey	M25/P21(S)	11.5	42.0 / 12.0	16.0	27.0	42.0 / 5.0	38.0	21.0 / 14.7	6.5	100
UHF 29	83621614	grey	M32/P29(S)	11.5	51.0 / 12.0	16.0	44.0	48.0 / 5.0	60.0	25.5 / 19.3	6.5	50
UHF 36	83621616	grey	M40/P36(S)	11.5	61.0 / 13.0	19.0	47.5	55.0 / 6.0	60.0	30.5 / 24.5	6.5	50
UHF 48	83621618	grey	M50/P48(S)	11.5	74.0 / 13.0	19.0	47.5	68.0 / 8.0	60.0	37.0 / 30.0	6.5	50

Dimensional drawing

