

Back

**Label sleeves KT (standard sleeve)**

High-quality, fully transparent label sleeves for labelling wires, cables and conduits. They hold the idents (BK) and the ACS labels type KS or DM.

- Seven different sizes are available for applications ranging from 0.22 – 120 mm<sup>2</sup>
- The sleeves come in different lengths

The special KT 2/20x9 or KT 2/35x9 sleeves are for multi-line single wire labelling. They hold the ACS labels type KSO or DM 9...

- 40 – 60 °C
- V0
- PVC
- Standard label sleeve
- Use in electrical systems and installations of all kinds



Type	Order no.	Application range from – to mm	Core cross section* from – to mm	for Label	Number of idents BK23 / BK30	Pack qty.
Sleeve length 18 mm (A)						
KT 2/18	86201814	2.5 – 4.0	0.75 – 2.5	KS 4/18; DM 4...	7 / 6	2000

**Polyvinyl chloride (PVC)**

Material: Polyvinyl chloride (PVC)

Soft PVC is made from polyvinyl chloride, softeners and process materials, e.g. stabilisers and lubricants. PVC is resistant to corrosive saline solutions and most acids.

Thermal stability: up to 60 °C Fire classification: V0 i.a.w. UL94

**Dimensional drawing:**



