

Back

Label sleeves KT (standard sleeve)

High-quality, fully transparent label sleeves for labelling wires, cables and conduits. They hold the idents (BK) and the ACS labels type KS or DM.

- Seven different sizes are available for applications ranging from 0.22 – 120 mm²
- The sleeves come in different lengths

The special KT 2/20x9 or KT 2/35x9 sleeves are for multi-line single wire labelling They hold the ACS labels type KSO or DM 9...

- 40 – 60 °C
- V0
- PVC
- Standard label sleeve
- Use in electrical systems and installations of all kinds



| Type | Order no. | Application range from – to mm | Core cross section* from – to mm | for Label | Number of idents BK23 / BK30 | Pack qty. |
|-------------------------|-----------|--------------------------------------|--|---------------------|---------------------------------|--------------|
| Sleeve length 18 mm (A) | | | | | | |
| KT 6/18 | 86201822 | 15.0 – 23.0 | 50.0 – 120.0 | KS 4/18; DM 4... | 7 / 6 | 300 |

Polyvinyl chloride (PVC)

Material: Polyvinyl chloride (PVC)

Soft PVC is made from polyvinyl chloride, softeners and process materials, e.g. stabilisers and lubricants. PVC is resistant to corrosive saline solutions and most acids.

Thermal stability: up to 60 °C Fire classification: V0 i.a.w. UL94

Dimensional drawing:



