






Back

KS label plate (multi-line) 

High-quality, halogen-free, universal label plate for single-line and multi-line inscription. The KS label plate is inserted in base holders BT, BTK or BZS.



-  -40 – 140 °C
-  V0
-  PC
-  Single-line and multi-line inscription
-  Use in electrical systems and installations of all kinds

Type	Order no.	Colour	RAL equiv.	Label size mm	Printable area mm	Number symbols/label	Trees per frame	Qty. each frame	Software Type	Pack qty.	
Label length 27 mm for BT 15/27, BTK 15/27, BT-SR 15x27 mm and BTK 22.5	KS 15/27	86361010	white	9016	15 x 27	15 x 27	15 / 3	4	16	85	480

PC polycarbonate

Material: Polycarbonate (PC)

Excellent surface gloss and transparency (natural), high mechanical strength and dimensional stability under heat, outstanding electrical and dielectric properties, superb dimensional accuracy and low water absorption. Impact resistance up to approx. 140 °C and, as a general rule, PC is self-extinguishing even without the addition of fire-retardants.

Thermal stability: up to 140 °C Dimensional stability: up to 1.8 N/mm 135 °C Flammability: V0 based on UL94 Halogen-free under DIN/VDE 0472, Part 815 UV-stabilised