


Back

**KS label plate (single-line)**



High-quality, halogen-free, universal label plate. The label plate KS 4/x is used with sleeves KT, KTH, KTHQ or holders KM, KMH, KMHQ or KTN on wires, cables, lines or conduits. The label plate is available in various lengths and colors. The large printable area at the top allows room for individual project reference, dispensing with the need to organise additional systems.



-40 – 140 °C



V0



PC



Single-line inscription



Use in electrical systems and installations of all kinds

Type	Order no.	Colour	RAL equiv.	Label size mm	Printable area mm	Number symbols/line	Trees per frame	Qty. each frame	Software Type	Pack qty.
KS 4/30	86361042	white	9016	4 x 30	4 x 30	16 / 1	1	34	15	1020

**PC polycarbonate**

Material: Polycarbonate (PC)

Excellent surface gloss and transparency (natural), high mechanical strength and dimensional stability under heat, outstanding electrical and dielectric properties, superb dimensional accuracy and low water absorption. Impact resistance up to approx. 140 °C and, as a general rule, PC is self-extinguishing even without the addition of fire-retardants.

Thermal stability: up to 140 °C Dimensional stability: up to 1.8 N/mm 135 °C Flammability: V0 based on UL94 Halogen-free under DIN/VDE 0472, Part 815 UV-stabilised

**Dimensional drawing:**



