

Back

**KSN label plate**



High-quality, halogen-free label plate for subsequent direct labelling of wires. The KSN label plate can be attached to wired single cores without disconnecting them. They can be fitted easily and quickly with the MW1 assembly tool.



-40 – 140 °C



V0



PC



Single-line inscription. Retrofitting.



Use in electrical systems and installations of all kinds

Type	Order no.	Colour	RAL equiv.	Application range from – to mm	Core cross section* from – to mm	Label size mm	Number symbols/line	Trees per frame	Qty. each frame	Software Type	Pack qty.
KSN- B	86381412	white	9016	2.6 – 3.0	1.0 – 1.5	14 x 5	7 / 1	1	36	13	360

**PC polycarbonate**

Material: Polycarbonate (PC)

Excellent surface gloss and transparency (natural), high mechanical strength and dimensional stability under heat, outstanding electrical and dielectric properties, superb dimensional accuracy and low water absorption. Impact resistance up to approx. 140 °C and, as a general rule, PC is self-extinguishing even without the addition of fire-retardants.

Thermal stability: up to 140 °C Dimensional stability: up to 1.8 N/mm 135 °C Flammability: V0 based on UL94 Halogen-free under DIN/VDE 0472, Part 815UV-stabilised

**Dimensional drawing:**

