


Back

Type KMR

High-quality, halogen-free snap-in label plates. Labels available for mounting individually or in strips. The large printable area at the top allows room for individual project and terminal block reference, dispensing with the need for additional organisational systems. Label plates designated as "5 - 6 mm-pitch strips" can be adapted to terminal block widths of 5 mm or 6 mm by means of a flexible connection.



- 40 – 140 °C
- V0
- PC
- Halogen-free terminal block labeling
- Individual and strip mounting

Type	Order no.	Colour	RAL equiv.	Label size mm	Printable area mm	Number symbols/line	Trees per frame	Qty. each frame	Software Type	Pack qty.
5 mm pitch strips in a row	KMR 86401016	white	9016	5 x 15	5 x 15	8 / 1	4	88	36	1400

PC polycarbonate

Material: Polycarbonate (PC)

Excellent surface gloss and transparency (natural), high mechanical strength and dimensional stability under heat, outstanding electrical and dielectric properties, superb dimensional accuracy and low water absorption. Impact resistance up to approx. 140 °C and, as a general rule, PC is self-extinguishing even without the addition of fire-retardants.

Thermal stability: up to 140 °C Dimensional stability: up to 1.8 N/mm 135 °C Flammability: V0 based on UL94 Halogen-free under DIN/VDE 0472, Part 815 UV-stabilised

Dimensional drawing:



KMR 5/10 FA (terminal block profile)



KMR 5/10 FA (label profile side view)



KMR 5/10 FA (label profile front view)



KMR 6/15-6.7 (terminal block profile)



KMR 6/15-6.7 (label profile side view)



KMR 6/15-6.7 (label profile front view)