

Back

KSO label plate

High-quality, halogen-free, universal label plate for single-line and multi-line inscription. The KSO label is used with sleeves KT... or holders KM, KMH on cables, lines or conduits. The label plate is available in various lengths and colors. The large printable area at the top allows room for individual project reference, dispensing with the need to organise additional systems.



- 40 – 140 °C
- V0
- PC
- Single-line and multi-line inscription
- Use in electrical systems and installations of all kinds

Type	Order no.	Colour	RAL equiv.	Label size mm	Printable area mm	Number symbols/line	Trees per frame	Qty. each frame	Software Type	Pack qty.
Label length 20 mm										
KSO 20x9	86421028	white	9016	20 x 9	20 x 9	11 / 2	4	20	64	680

PC polycarbonate

Material: Polycarbonate (PC)

Excellent surface gloss and transparency (natural), high mechanical strength and dimensional stability under heat, outstanding electrical and dielectric properties, superb dimensional accuracy and low water absorption. Impact resistance up to approx. 140 °C and, as a general rule, PC is self-extinguishing even without the addition of fire-retardants.

Thermal stability: up to 140 °C Dimensional stability: up to 1.8 N/mm 135 °C Flammability: V0 based on UL94 Halogen-free under DIN/VDE 0472, Part 815 UV-stabilised

Dimensional drawing:



