

Suonerie industriali

Industrial bells

V 12-24-48-60-110-240 (±10%)		50 Hz	* 60 Hz	On ∞
autoestinguente self-extinguishing	IP 66			°C -30 +50
				M 16



CEAD 165 R **CEADEL 165 R**
CD165R CDL165R



CEAD 165 G **CEADEL 165 G**
CD165G CDL165G




CEAD 165

V	12	24	48	60	110	240
mA	860	430	250	170	90	50
dB(A)1m	100	100	100	100	100	100
Hz	2000÷12000					

CEADEL 165

V	12	24	48	60	110	240
mA	600	300	160	120	60	28
dB(A)1m	98	98	98	98	98	98
Hz	2000÷12000					



Cead Kg. 1,35
Ceadel Kg. 1,0

CEAD165R12A	54090	CDL165R12D	54097
CEAD165R24A	54091	CDL165R24D	54098
CEAD165R48A	54092	CDL165R48D	54099
CEAD165R110A	54094	CDL165R60D	54100
CEAD165R240A	54096	CDL165R110D	54101

CEAD165G12A	54070	CDL165G12D	54080
CEAD165G24A	54071	CDL165G24D	54081
CEAD165G48A	54072	CDL165G48D	54082
CEAD165G110A	54074	CDL165G60D	54083
CEAD165G240A	54076	CDL165G110D	54084
		CDL165G240D	54087

* 60 Hz a richiesta. 60 Hz on request.

Suoneria industriale stagna

Waterproof industrial bell

V 12-24-48-60-110-240 (±10%)		50/60 Hz	On ∞
autoestinguente self-extinguishing	IP 66		°C -30 +50
			M 16



SIAD 215 NAVE
STSD215N

SIADEL 215 NAVE
STSDL215N



INOX
STAINLESS STEEL


SIAD 215 NAVE

V	12	24	48	60	110	240
mA	860	430	250	170	90	50
dB(A)1m	100	100	100	100	100	100
Hz	1000÷15000					

SIADEL 215 NAVE

V	12	24	48	60	110	240
mA	600	300	160	120	60	28
dB(A)1m	98	98	98	98	98	98
Hz	1000÷15000					

STSD215N12A	91960	STSDL215N12D	91967
STSD215N24A	91961	STSDL215N24D	91968
STSD215N48A	91962	STSDL215N48D	91969
STSD215N60A	91963	STSDL215N60D	91970
STSD215N110A	91964	STSDL215N110D	91971
STSD215N240A	91966	STSDL215N240D	91973



Siad Nave Kg. 2,7
Siadel Nave Kg. 2,8