



Part No.: 31950
CUSTO®EasyLiner
DII bus-mounting fuse base, gauge screw shrouded

3-pole, busbar 12 - 30 mm, combination base for 5 and 10 mm thick busbars and double-T- and triple-T-section
latching mechanism when sliding onto busbar
open box terminal 1.5 - 25 mm²

System :
60mm-System classic

Standards :
IEC 60269-1:2006
IEC 60269-3:2006
EN 60269-1:2007
HD 60269-3:2007
DIN EN 60269-1/03.08
DIN VDE 0636-3/03.08

Approvals :
Germanischer Lloyd, GOST

Electrical Data :
500 V / 25 A

Power dissipation:
The power dissipation of the device results in 0,8 W at a typical load with 80 % of the nominal current.
(The power dissipation is 1,2 W for application at nominal current.)

for fuses and screw-in gauge rings according to DIN VDE 0636-3
50 kA short-circuit withstand capability

Wöhner reserves the right to make modifications to its components, as the result of developments and technical advances.

Mechanical Data :

Width x Height x Depth (mm): 42 x 200 x 43

Weight (g): 287

E27

Fastening method:

latching mechanism to prevent displacement

contact pressure provided by screw cap

box-terminal tightening torque 3 Nm

Material Characteristics :

Main body:

temperature stability 140°C,

self-extinguishing in acc. to UL 94,

creepage resistance CTI 225,

silicon-free, halogen-free

Screws:

+/- (PZ2), galvanized, chromized

Contacts:

direct contact the fuse onto busbar

over a silver copper plate

Accessories to Article 31950 :

01098 D-screw cap, porcellain

500 V

31098 D-screw cap, plastic

500 V

31911 locking cap DII

500 V

31905 locking cap DII

500 V